

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04L 12/64, 12/56		A1	(11) International Publication Number: WO 00/62497
			(43) International Publication Date: 19 October 2000 (19.10.00)
(21) International Application Number: PCT/US00/09993 (22) International Filing Date: 14 April 2000 (14.04.00) (30) Priority Data: 09/291,889 14 April 1999 (14.04.99) US (71) Applicant: EXCEL SWITCHING CORPORATION [US/US]; 255 Independence Drive, Hyannis, MA 02601 (US). (72) Inventor: LOCASCIO, Timothy, Ray; 424 Old Mill Road, Osterville, MA 02655 (US). (74) Agents: ATTAYA, Michael, E. et al.; Cesari and McKenna, LLP, 30 Rows Wharf, Boston, MA 02110 (US).			(81) Designated States: AE, AL, AU, BA, BB, BG, BR, CA, CN, CR, CU, CZ, DM, EE, GD, GE, HR, HU, ID, IL, IN, IS, JP, KP, KR, KZ, LC, LK, LR, LT, LV, MA, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, TR, TT, UA, UZ, VN, YU, ZA, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: VOICE/DATA ACCESS CONCENTRATION FOR NODE IN AN EXPANDABLE TELECOMMUNICATIONS SYSTEM



(57) Abstract

Apparatus operable as a standalone, open programmable switch, a node, an expandable telecommunications system, or a gateway includes a voice/data access concentrator (VDAC) card for providing voice over IP (Internet protocol) capability. The VDAC card includes an array of digital signal processors (DSPs) which may be programmed to perform desired protocol conversions between circuit-based protocols, such as T1, E1 or J1, and packet-based protocols, such as IP. The apparatus is scalable and may readily incorporate other cards which provide both subscriber supplementary services and network signalling as required to meet the needs of a particular application.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

VOICE/DATA ACCESS CONCENTRATION FOR NODE IN AN EXPANDABLE TELECOMMUNICATIONS SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention.

5 The present invention relates generally to the field of telecommunications and, more specifically, to a programmable telecommunications switch which is operable as a node in an expandable telecommunications system and includes an interface for conducting telecommunications over the Internet.

2. Discussion of the Related Art.

10 With the goal of providing telecommunication services at lower prices than those charged by long distance carriers, competitive local exchange carriers (CLECs) and government-controlled telephone companies, an effort is underway to use the Internet to carry voice traffic which has traditionally been carried by the public switched telephone network (PSTN). This type of application or service is often referred to as
15 “voice over IP” (VoIP) where “IP” refers to Internet protocol.

 Several important considerations arise in connection with the development of VoIP including determining how much, if any, of a communication path from a given subscriber to another should be provided by the PSTN and how much should be provided by the Internet. In other words, should a subscriber’s communication device interface directly with the Internet (meaning that subscribers must be equipped with
20 “Internet telephones,” PCs which include telephone functionality or the like), or should the PSTN be used to connect subscribers (who would continue to use conventional telephone sets) to the Internet through a gateway or similar device. Of course, other scenarios are possible as well, and it is likely that a mixed or hybrid infrastructure will
25 exist for a long time because of the prohibitive cost of constructing or replacing networks as well as replacing subscriber equipment.

Another consideration is how to provide supplementary or enhanced services to subscribers who will not want to sacrifice call forwarding, call-waiting, voicemail, conference calling and other existing services merely to obtain lower cost Internet-based phone service. Further, there is great need for system flexibility to allow rapid, inexpensive development and introduction of new services, largely because such new services provide large revenue growth potential for most carriers.

A third consideration is system capacity and scalability. Because of the difficulty in accurately forecasting both the demand for additional telecommunication bandwidth and the rate at which subscribers will migrate to Internet-based telephony, it is extremely important that any system be capable of rapid, large-scale expansion without significant disruption of service and without forcing large initial investment for capacity that may not be needed for a long time.

SUMMARY OF THE INVENTION

In brief summary, the present invention provides a programmable telecommunication switch, operable as a node in an expandable telecommunications system, as a standalone switch, or as a gateway. The programmable switch includes an interface, sometimes referred to as a voice/data concentrator card, for conducting VoIP communications. One side of the interface connects to the Internet or other packet-based network, while the other side of the interface connects with the switch's internal bus structure over which the interface and other circuitry within the switch may communicate.

The present invention permits a CLEC, system integrator or other customer to introduce VoIP capability as either an addition to an existing network (e.g., PSTN) or through the construction of a new network as desired. In either case, the present invention allows the introduction of VoIP capability in the locations and amounts needed to satisfy demand. Future growth in demand for such capacity is flexibly accommodated by simply including additional interfaces within the switch or adding additional nodes as the case may be. If desired, multiple interfaces may be concentrated in a single node whose VoIP capability is fully accessible by the other nodes of the expandable tele-

communications system. Similar considerations apply to using the present invention to provide communications based on protocols other than IP.

In addition, traditional telephony services and functions, including both supplementary services (conferencing, call waiting, voicemail, etc.) and network signalling (tone detection, tone generation, etc.), as well as new services, may be provided within the same programmable switch which includes a VoIP capability or within other nodes that are part of the same expandable telecommunications system.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention description below refers to the accompanying drawings, of which:

Fig. 1 is block diagram of a programmable telecommunication switch which is operable as a standalone device, a node in an expandable telecommunications system or as a gateway, and which is constructed in accordance with a preferred embodiment of the present invention; and

Fig. 2 is a block diagram of the VDAC card shown in Fig. 1.

DETAILED DESCRIPTION OF AN ILLUSTRATIVE EMBODIMENT

Figure 1 shows the major functional components of a preferred embodiment of a programmable telecommunications switch 2 in which the present invention may be implemented. Circuit-based network/line interfaces 4, which may represent links to a public switched telephone network (PSTN) or private circuit-based/circuit-switched network (or both), are provided by a series of line card input/output (IO) cards 20. If desired, a redundant IO card 22 and redundant IO bus 24 may optionally be included.

One or more digital network (T1, E1 or J1) or analog trunk/line line cards 26 communicate with IO cards 20 over line card (LC) IO lines 28. Line cards 26 are also connected in communicating relationship with redundant switching buses 30a and 30b. Again, if desired, one or more redundant line cards 32 may be provided, such redundant line cards arranged to communicate with a redundant IO card 22 over redundant LC IO lines 34.

If desired, diverse, programmable communications services such as tone detection and generation, sub-rate switching, conferencing, voice recorded announcements, call progress analysis, speech recognition, ADPCM compression, interactive voice response (IVR) and many others may be provided by one or more multifunction digital signal processing (MFDSP) cards 36 and optional redundant cards.

If desired, a Signalling System No. 7 (SS7) card 38 supports communications over network/line interfaces 4 using the SS7 protocol. As noted above with respect to other types of cards, one or more optional redundant SS7 cards 38 may be provided within switch 2.

One or more voice/data access concentrator (VDAC) cards 48 (which may include an optical n+1 VDAC card) are connected in communicating relationship with switching buses 30a and 30b. VDAC cards 48 provide packet-based network interfaces 50 for connection with the Internet (not shown) or other packet-based networks whose communication protocols are supported by cards 48.

It should be understood that by providing other types of cards within switch 2, other communication protocols such as ISDN, DS3, SONET, ATM or others may also be supported by switch 2.

Control of the operations of switch 2, as well as the actual switching functions, are performed by either a CPU/matrix card or nodal switch 44a. If a CPU/matrix card is used, switch 2 may operate essentially as a standalone device (i.e., as opposed to operating as a switching node in an expandable telecommunications system, described below) or as a gateway between PSTN network/line interfaces 4 and packet-switched network interfaces 50. In that case, the CPU/matrix card 44a may be connected to a host interface 42a through which communications with an external host device (not shown) are effected. Typically, but not necessarily, the overall operations of switch 2 are controlled by an application program running on the host device.

Alternatively, if a nodal switch is used, switch 2 may operate as a node in an expandable telecommunications system, an example of which is described in U.S. Patent 5,544,163 which is hereby incorporated by reference. In such an embodiment, the nodal switch 44a is preferably connected with a ring IO card 40a through which communications with an inter-nodal network 12a are effected. Inter-nodal network 12a is

preferably implemented with one or more fiber optic rings. The nodal switch 44a may also communicate with an external host via host interface 42a.

Regardless of whether a CPU/matrix card or a nodal switch is selected, a matching standby CPU/matrix card or nodal switch 44b may optionally be provided and accompanied by the appropriate host interface 42b or ring IO card 40b (or both). In such a configuration, a link 46 is provided for direct communication between active and standby devices 44a and 44b.

Details of the construction and operation of an exemplary CPU/matrix card, as well as switching buses 30a and 30b, may be found in U.S. Patent 5,349,579 which is hereby incorporated by reference. Similarly, details of the construction and operation of an exemplary nodal switch may be found in the above-referenced U.S. Patent 5,544,163.

Figure 2 is a detailed block diagram of VDAC card 48 shown in Figure 1. An ethernet switch 54 provides dual network interfaces 50 which are capable of operating at 100 Mbit/sec. Ethernet switch 54 is interfaced with a CPU 52, which is preferably a Motorola MC860, that controls overall operation of VDAC card 48. CPU 52 communicates over dual HDLC buses which are part of switching buses 30a and 30b.

A local control map 56, which is under the control of CPU 52, operates in conjunction with a time division multiplex (TDM) bus switch 58, to time switch data (timeslots) between switching buses 30a and 30b and VDAC card 48. Timeslots which are received from buses 30a and 30b, via TDM bus switch 58, are passed to PCM memory 60 and then to PCM/module switch 62, whose operation is controlled by module control map 64.

As the timeslots are passed through switch 62, they are routed to one of eight Texas Instruments TI320C549 Digital Signal Processors (DSPs) 80a-80d on one of four VoIP daughter cards (each is denoted by a dashed line box). Each daughter card includes eight DSPs and their own external SRAM 81a-81d. The DSPs are memory mapped into the address space of a Motorola MC850 processor 74a-74d, used to control the operation of the daughter card, which has its own local SDRAM 78a-78d and flash memory (not shown). Each processor 74a-74d has a 10 Mbit/sec full duplex ethernet

pipe to ethernet switch 54 which allows for communication among all of the daughter cards, CPU 52 and the external IP network.

CPU 52 is also connected in communicating relationship with external bus arbitration logic 66, external bus buffers 68, SDRAM 70 and flash memory 72.

5 In general, VDAC card 48 functions to provide internetworking between packet-switched or packet-based communication protocols (e.g., IP) that are typically used to effect communications over network interfaces 50, and circuit-switched or circuit-based communication protocols (i.e., T1, E1 or J1) that are typically used to effect communications over network/line interfaces 4 (Fig. 1). DSPs 74a-74d, along with
10 their related circuitry, operate to perform the necessary steps, including packetizing and depacketizing, digital processing of data and the like, to convert from one protocol to another. For example, by loading appropriate software into memories 70 and 72, CPU 52 may simultaneously run H.323, H.225 (Q.931) and H.245 protocols or a variety of other protocols chosen to meet the needs of a particular application, thereby enabling
15 VDAC card 48 to support communications which use any of those protocols. Such protocol software may be obtained from commercial sources, one such source for H.323 software being RADVision Inc. of Mahwah, New Jersey.

With reference to Figures 1 and 2, an example of the protocol conversion which may be performed will now be described. Assume that one or more T1 spans are connected to circuit-based network/line interfaces 4. Further assume that packet-based
20 network interfaces 50 are connected to the Internet for the purpose of providing VoIP service within switch 2. As timeslots (e.g., PCM data) which are destined for the Internet arrive at T1 line cards 26, they are transmitted over switching buses 30a and 30b to TDM bus switch 58 on VDAC card 48. TDM bus switch 58 time switches those time
25 slots to PCM memory 60, from which they pass through PCM/module switch 62 and then to designated areas of DSP external SRAM 81a-81d. Once stored in SRAM 81a-81d, the timeslots are available for processing by the respective one of DSPs 80a-80d that has access to such SRAM. Such processing may typically include packetization of the timeslots as data within IP packets, which packets are then passed via the processor
30 74a-74d through the ethernet buses 82a-82d to ethernet switch 54 for transmission to the Internet.

It will be understood by those skilled in the art that VDAC card 48 may also perform a protocol conversion which is essentially the reverse of the process just described, that is, receiving Internet packets containing timeslots at ethernet switch 54, depacketizing the timeslots, and passing those timeslots via TDM bus switch 58 to
5 switching buses 30a and 30b, over which such timeslots may be passed to line cards 26, MFDSP cards 36, SS7 cards 38 CPU/matrix cards or nodal switches 44a and 44b.

The foregoing description has been limited to a specific embodiment of this invention. It will be apparent, however, that variations and modifications may be made to the invention, with the attainment of some or all of the advantages of the invention.
10 Therefore, it is the object of the appended claims to cover all such variations and modifications as come within the true spirit and scope of the invention.

What is claimed as new and desired to be secured by Letters Patent of the United States is:

CLAIMS

- 1 1. Apparatus operable as a node in a expandable telecommunications system, said
2 apparatus comprising:
3 one or more nodal switches each of which includes circuitry for transmitting and
4 receiving information over an inter-nodal network to which said node and other nodes
5 of said system are connected in communicating relationship;
6 one or more line cards, connected in communicating relationship with said one
7 or more nodal switches, for interfacing with one or more circuit-switched networks
8 over which communications are conducted using circuit-switched protocols; and
9 a voice/data concentrator card, connected in communicating relationship with
10 said one or more nodal switches, and with one or more packet-switched networks over
11 which communications are conducted using packet-switched protocols including Inter-
12 net protocol, for internetworking between said circuit-switched protocols and said
13 packet-switched protocols.
- 1 2. Apparatus as in claim 1 wherein said concentrator card includes a plurality of
2 digital signal processors and at least one of said processors is programmed to receive
3 timeslots from said one or more line cards or nodal switches, create packets in which
4 said timeslots are carried as data, and transmit said packets over said one or more
5 packet-switch networks.
- 1 3. Apparatus as in claim 2 wherein said at least one processor is further pro-
2 grammed to receive packets from said one or more packet-switched networks, extract
3 timeslots carried as data in said packets, and transmit said timeslots to said one or more
4 line cards or nodal switches.
- 1 4. A method of providing voice over Internet protocol (VoIP) in an apparatus op-
2 erable as a node in an expandable telecommunications system, said method comprising
3 the steps of:

4 at a voice/data access concentrator card which includes an interface to a packet-
5 switched network, receiving Internet protocol packets and extracting therefrom data
6 representing voice;
7 if necessary, converting said extracted data into timeslots;
8 passing said timeslots to either a line card which includes an interface to a cir-
9 cuit-switched network or, alternatively, through a switch and then to said line card, and
10 transmitting said timeslots over said circuit-switched network;
11 receiving timeslots at said line card and passing them to said concentrator card
12 or, alternatively, through said switch and then to said concentrator card;
13 if necessary, converting said timeslots into a format compatible for packetiza-
14 tion;
15 creating Internet protocol packets which carry said timeslots or converted time-
16 slots as data; and
17 transmitting said packets over said packet-switched network.




FIG. 1

2/4






FIG. 2A





INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/09993

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L12/64 H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y A	US 5 544 163 A (MADONNA ROBERT P) 6 August 1996 (1996-08-06) figures 1A, 1E, 2A, 2C, 8A, 8B column 6, line 19 - line 21 column 8, line 61 - column 9, line 18 column 10, line 46 - line 57 claim 50	1-3 4
Y A	US 4 903 261 A (MARGGRAFF LEWIS J ET AL) 20 February 1990 (1990-02-20) figures 1, 2, 3A, 7 column 2, line 40 - column 3, line 40 column 6, line 19 - line 58 column 7, line 12 - line 34	1-3 4
	-/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *A* document member of the same patent family

Date of the actual completion of the international search

4 September 2000

Date of mailing of the international search report

11/09/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Lamadie, S

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/09993

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 99 05830 A (ERICSSON TELEFON AB L M) 4 February 1999 (1999-02-04) figures 3,6 page 4, line 1 - line 31</p>	4

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/09993

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5544163 A	06-08-1996	AU 693182 B	25-06-1998
		AU 2105195 A	25-09-1995
		BG 100814 A	30-05-1997
		BR 9507002 A	16-09-1997
		CA 2184726 A	14-09-1995
		CN 1147322 A	09-04-1997
		CZ 9602493 A	16-04-1997
		EP 0749653 A	27-12-1996
		FI 963516 A	06-09-1996
		HU 76610 A	28-10-1997
		JP 11341067 A	10-12-1999
		JP 11341068 A	10-12-1999
		JP 11341069 A	10-12-1999
		JP 11341070 A	10-12-1999
		JP 9505190 T	20-05-1997
		NO 963730 A	24-10-1996
		NZ 283096 A	28-07-1998
		NZ 330410 A	28-01-1999
		NZ 330411 A	28-01-1999
		PL 316841 A	17-02-1997
		US 6002683 A	14-12-1999
		WO 9524788 A	14-09-1995
		US 5737320 A	07-04-1998
		US 5864551 A	26-01-1999
US 4903261 A	20-02-1990	US 4771425 A	13-09-1988
		DE 3586031 A	17-06-1992
		EP 0179979 A	07-05-1986
		JP 5276243 A	22-10-1993
		JP 2527931 B	28-08-1996
		JP 61107856 A	26-05-1986
		US 4819228 A	04-04-1989
WO 9905830 A	04-02-1999	AU 8363298 A	16-02-1999